



**ET 型 / ET Core**

| 型号<br>TYPE      | 图例<br>FIG. | 尺寸 Dimensions ( mm ) |               |         |          |                 |          |         |
|-----------------|------------|----------------------|---------------|---------|----------|-----------------|----------|---------|
|                 |            | A                    | B             | C       | D        | E               | F        | G       |
| ET20            | 1          | 20.1±0.4             | 20.1±0.4      | 4.4±0.2 | 4.0±0.2  | 16.1±0.3        | 16.1±0.3 | 6.1max  |
| ET20.1/26.3/5.4 | 1          | 20.1±0.4             | 26.3±0.5      | 5.4±0.2 | 4±0.2    | 16.1±0.4        | 21.6±0.4 | 2±0.15  |
| ET20.3/26.3/5.5 | 1          | 20.3±0.4             | 26.3±0.5      | 5.5±0.3 | 4±0.2    | 16.3±0.4        | 21.6±0.4 | 2±0.15  |
| ET23B           | 1          | 23.4±0.3             | 22.0±0.3      | 3.8±0.2 | 3.8±0.2  | 18.9min         | 17.4min  |         |
| ET24            | 1          | 24+0.7/-0.4          | 24+0.7/-0.4   | 4±0.3   | 4±0.2    | 18.9min         | 18.9min  |         |
| ET24D           | 1          | 24.0+0.7/-0.4        | 24.0+0.7/-0.4 | 4.0±0.3 | 4.0±0.2  | 19.2min         | 19.2min  |         |
| ET25E           | 2          | 24.5+0.7/-0.3        | 24.5+0.7/-0.3 | 7±0.3   | 6.6±0.2  | 19.5+0.85/-0.15 | 19.3min  |         |
| ET25B           | 1          | 25.5±0.5             | 25.5±0.5      | 5.0±0.3 | 5.0±0.3  | 19.2min         | 19.2min  |         |
| ET28/34.8/6.4   | 1          | 28±0.5               | 34.8±0.5      | 6.4±0.3 | 6.4±0.3  | 22±0.4          | 28.8±0.5 |         |
| ET28A           | 1          | 28.7±0.5             | 28.7±0.5      | 5.0±0.3 | 5.0±0.3  | 22.2min         | 22.2min  |         |
| ET35B           | 1          | 35.3±0.6             | 35.3±0.6      | 7.5±0.3 | 7.5±0.25 | 27.3±0.5        | 27.3±0.5 | 10.2max |

| C1 | Ae    | Le    | Amin  | AL(±30%) |      |      |       | 重量<br>g/PCS |
|----|-------|-------|-------|----------|------|------|-------|-------------|
|    |       |       |       | TS10     | TS13 |      |       |             |
|    |       | 50.58 | 17.60 | 80.30    |      | 4300 | 5600  | 4.60        |
|    |       | 61.89 | 21.60 | 103.90   |      | 4500 | 5900  | 7.20        |
|    | 22.78 | 62.09 | 22.00 | 114.40   |      | 4600 | 5900  | 7.30        |
|    | 15.09 | 57.17 | 14.44 | 82.80    |      | 3300 | 4200  | 4.50        |
|    | 17.64 | 61.11 | 16.00 | 107.90   |      | 3600 | 4700  | 5.60        |
|    | 16.98 | 61.88 | 16.00 | 105.80   |      | 3400 | 4400  | 5.50        |
|    | 37.23 | 60.12 | 34.30 | 138.40   |      | 7700 | 10000 | 11.60       |
|    | 27.35 | 62.60 | 25.00 | 112.00   |      | 5500 | 7200  | 8.60        |
|    | 39.29 | 82.71 |       | 151.90   |      |      |       |             |
|    | 27.87 | 71.61 |       |          |      | 4900 | 6300  | 10.40       |
|    | 58.59 | 86.69 |       |          | 6500 | 8600 | 11000 | 26.40       |